


— ITALIAN ENERGY —

# BRIGHTER FUTURE





# **Hydrogen GT Enclosure open issues for operation**

Ansaldo Energia / Daniel Bruggmann

Bergen, 26.03.2025

## Table of contents

- Targets for H2 readiness for Enclosure
- GT enclosure
- Iteration steps
- Summary of solution approaches



## Targets for H2 readiness

The target of the study was to find a way to operate the GT enclosure safely on hydrogen with the lowest possible costs for the entire project.

This attempts were made to achieve this only by changing the ventilation installation.

### Safety standards:

UK Health and safety code PM84, augmented by HSE publications CM/04/09

IEC60079-10-1

NFPA497 / NFPA2

ISO 21789


(All norms and standard documents are still written for methane.

These norms for H2 are currently under development.)

### Boundary conditions for a safe operation of the enclosure (used for the CFD Study):

- A gas leakage through a hole between 0.25 – 25 mm<sup>2</sup> has to be considered (worst case scenario to be considered)
- The size of a gas cloud (100% LEL) in such event should not exceed 1 m<sup>3</sup>

## Model of GT 26 enclosure




Dimension Enclosure  
12m x 12m x 12m

Air Flow  
Min: 9 m<sup>3</sup>/s  
Max: 50 m<sup>3</sup>/s

## Gas detection points in GT ventilation outlet duct



Pos. M3,M4: Standard Position of gas detectors GT enclosures

Pos M1-M10: CFD Gas concentration readings







## FDS design for GT26 / GT36




Used flanges  
Raised face  
flange (RF)



FDS second  
combustor GT26  
~48Flanges




FDS first  
combustor GT26  
~96Flanges



FDS GT36  
~200Flanges

All flange connections are potential leakage points

## Hydrogen explosive Cloud on leakage point A







## Iteration 1 – metallic cover (cuff) over flange

Boundary conditions:

- Hydrogen nest after 17 s
- Recirculating air: 9 m<sup>3</sup>/s



Volume of H2 Nest: 67.71 (m<sup>3</sup>)

## Result Negative


Metallic cover over flanges does not decrease the cloud size (the volume of gas is defined by crucial expansion)

The cloud size may even be increased.

The ventilation air flow was still not strong enough to blow out the H<sub>2</sub> cloud.

## Iteration 2 – ventilation air ducts below FDS

New Equipment  
Recirculation ventilation:  
Holes 5 cm diameter




### Result Positive

Ventilation air ducts increase the air exactly at the location around the FDs, where leakage appears.  
(leakage cloud will be diluted exactly at the location where it appears)

## Iteration 3 – ventilation air ducts below FDS

Hydrogen nest after 4 s (target: reduce gas detection reaction time to 4 s.)

- Recirculating air: 25 m<sup>3</sup>/s, supply air: 9 m<sup>3</sup>/s
- No cuff installed




### Result Positive

Ventilation air ducts increase the air exactly at the location around the FDs, where leakage appears.  
(leakage cloud will be diluted exactly at the location where it appears)

## Iteration 4 – Increase ventilation air flow

Hydrogen nest after 4 s (target: reduce gas detection reaction time to 4 s.)

- Recirculating air: 25 m<sup>3</sup>/s, supply air: 20 m<sup>3</sup>/s (increase main air ventilation from 9 m<sup>3</sup>/s to 20 m<sup>3</sup>/s)
- No cuff installed



## Result Neutral

Small increased normal ventilation air flow does not have a considerable impact on leakage cloud size

## Possible Design Changes:

### 1. Reduce leakage in the worst case.

- To reduce the size of the leakage, a different flange system needs be used in the gas system. This new flange system should have a lower standard leakage rate.
- Which flange design will have the necessary low leakage rate has to be worked out in a separate process. This can be done as soon as the detail design for all H<sub>2</sub> components is carried out.




## Possible Design Changes:

### 2. Reduce leakage time

- To reduce the time between the leak occurring and the leak being detected, the gas sensors must be moved as close as possible to the possible leak positions. The sensors must also have a much faster response time.
- Improvement of air flow in the enclosure with additional Fans below the FDS

### 3. Extraction of leakage gas.

- An extraction system has been developed to extract liquid fuels, and we considered to adapt it to extract hydrogen leakages and transport them to the outside via a separate system.



As it is visible the way to operate the enclosure safely on H<sub>2</sub> is not yet done, but there is a way to do it.



**Thank you for your attention**