


H₂ Readiness, Challenges and Solutions – the OEM View”

Dr. Adnan Eroglu
Senior Principal Key Expert
Siemens Energy, Gas Services



2023 was the warmest year on record. By a record margin!

Global surface air temperature (July)




Source: C3S, on behalf of EU Commission; Documentary "Voice of the glaciers"



Decarbonization pathways for gas turbines

Hydrogen, sustainable fuels or carbon capture?



Zero Emissions via Hydrogen Combustion

Fuel Characteristics

Differences of hydrogen and natural gas as a fuel in gas turbines

H₂ Properties are different from NG

Hydrogen has lower density & volum. energy content (~1/3 of NG)
Prone to leakage. Requires larger flows to be handled by fuel system, but the Wobbe Index remains in natural gas range, i.e., 37 – 49 MJ/Nm³.

Hydrogen has wider flammability limits (H₂: 4-75% NG: 5-15%)
Much wider range of fuel/air-ratio to burn compared to natural gas. Adaption required of ventilation and gas detection system as well as fuel system.



Hydrogen has lower ignition energy (~15 times lower than NG)
Only a fraction of ignition energy is needed to get H₂ “going” compared to natural gas

Hydrogen auto-ignites & burns faster (up to 10x faster than NG)
H₂ combustion moves flame closer to injector – avoidance of “flash-back” by optimizing air and fuel distribution.

Risk of changing combustion pressure pulsations may damage hardware.

Hydrogen has higher flame temperature (~200°C higher than NG)
Potential for increased NO_x emissions from unmixed regions.

Hydrogen Reactivity



NOx emissions are dependent of the fuel used

NOx emissions are usually measured in **relative concentration** units (ppm, mg/Nm³), referenced to dry exhaust and 15% O₂ content in exhaust

When burning hydrogen, due to the much higher water content in the exhaust gas and lower flue gas volume, the calculated NOx values are **overinflated by up to 37.2%**

→ A **new emission unit is required** to provide a true and fair comparison of different fuels and power generation technologies (e.g. with a fuel correction factor or measurement in mg/kWh energy output).




Figure 1. Energy-based emissions correction factor for increasing hydrogen content in natural gas

Source: Position Paper by European Turbine Network, 2023

“H2 Readiness” and “H2 Capability” does not mean the same!

Step 1: H₂ Readiness

A power plant is considered H₂ ready if the powerplant is pre-equipped upfront for a future retrofit to the defined level of H₂. The pre-equipment is an optimization between initial investment and later retrofit costs and allows for a later conversion with economically reasonable costs/disruption

Step 2: H₂ Capability

A power plant is considered “H₂ capable” if all the installed equipment is fully capable of operating up to that defined level of H₂.

Examples:

- 50% “H₂ readiness” means the plant is designed for operation with natural gas, but already prepared for a later retrofit to 50% hydrogen capability
- 30% “H₂ capability” means the plant can operate with up to 30% hydrogen content without any additional changes
- A new plant built “100% H₂ ready” and “30%H₂ capable” means the the plant can operate at 30% initially and is prepared for a later retrofit to 100% capability



H2 Ready Concept with TÜV Süd Certificate

SE is able to offer H₂ ready power plants to customer H₂ requirements



- New build power plants prepared for later retrofit to hydrogen (“H₂ ready plants”) when immediate H₂ operation is not required/possible yet:
 - Optimized equipment configuration meeting future plant H₂ roadmap.
 - Plant with low additional front-end investments.
 - Offering allows for future H₂ retrofit with low costs/disruptions.
 - Backed by TÜV Süd Certification scheme for bidding, construction and retrofit phases

TÜV Süd Concept Certificate for Bidding Phase



The Certificate confirms that SE offering is H₂ ready according to technical requirements and customer specific boundary conditions considering:

Areas:

Fuel Supply:
Gas Turbine:
Fire/Ex Protection:
HRSG:
I&C & Electrical:
Safety:


Equipment/Systems considered:

Materials, sizing, aux. fuel, metering, additional systems...
Combustion System, Burner, Package Systems, etc.
Fire/Ex protection concepts, space provision for inert. system
Materials, temperatures, purging requirements
Design acc. to IIC*
Safety Integrity Levels definition and design

*or equivalent NFPA requirement, e.g. “NEC 500 Class I Div. 2 Group B.”

Hydrogen co-firing capabilities of Siemens Energy gas turbines

Heading towards 100% with full fuel flexibility H₂ ↔ Natural Gas




Power output in MW at ISO ambient conditions and natural gas

¹ Compared with 100% natural gas operation

■ DLE burner ■ WLE burner ■ Diffusion burner with unabated NO_x emissions

Hydrogen as a Gas Turbine Fuel

100% H₂ DLE requires extensive combustion technology developments.
0%-100% H₂ in Natural Gas DLE was demonstrated in SGT-400 in 2023.




H2-Ready power plants are increasingly being offered and contracted throughout the world.



- 7 Gas Turbines under construction prepared for later retrofit to H₂ operation (“H₂-ready”), but to run initially on natural gas
- These units also show in partial actual capability to run on hydrogen, but availability and/or business case for H₂ operation not yet there.

 H₂-ready plants in commercial operation with natural gas

 Units under construction as H₂-ready plants





Combined heat and power plant

Customer: Stadtwerke Leipzig GmbH

Country: Germany

Commercial operation: 2022

Reference HKW Leipzig Süd, Germany

Challenge



- New gas power plant to substitute existing heat supply from nearby lignite power plant
- Successive conversion from natural gas to hydrogen operation
- The plant is expected to **operate with 30 to 50 percent green hydrogen** only a few years after start of commercial operation
- The long-term goal is to operate the facility with **100 percent green hydrogen**

Solution



- The new gas power plant, with combined heat and power technology, will produce electricity and district heat for the city
- Successive conversion to hydrogen operation paves the way for Leipzig's decarbonization
- Electrical capacity of ~125 MW and thermal capacity of ~163 MW
- Up to 93% plant fuel efficiency thanks to district heat production (41% electrical efficiency)
- Commissioning scheduled for end of 2022

Technology



- 2 x SGT-800 62 MW gas turbines
- 2 x SGen-100A generators
- SIESTART battery energy storage system
- Long term service contract over a period of 15 years

Benefits



- High electrical and total plant efficiency
- Lowest emissions in its class with outstanding high fuel flexibility
- Competitive lifecycle costs
- Reliable and secure combined heat and power plant with black start capability
- Sustainable and future proof district heating power plant



60% Hydrogen at 25ppm NO_x

Customer: Braskem

Country: Brazil

Commercial operation: 2022

Hydrogen gas turbine reference Braskem, Brazil

Challenge



- Low cost for O&M
- Use of hydrogen as fuel gas to reduce use of natural gas, up to 60% but not exceeding 25 ppm NO_x
- Reduced need for external grid supply
- High availability and reliability

Solution



- Advanced Additive manufactured burners capable for 100% H₂
- Complete plant delivery, Siemens Energy will build, own & operate the CHP, HRSG and gas compressor
- O&M contract based on delivery of steam and power

Technology



- 2x SGT-600 PG with 3rd generation DLE system for up to 60% H₂ co-firing at 25ppm NO_x
- Operation at up to 88% H₂ blending rate has been demonstrated



Benefits



- Fuel cost savings operation on high levels of hydrogen in DLE, no need for water injection
- Lowest emissions using the latest DLE combustion system and control system <25 ppm NO_x
- Predictable operation and maintenance cost
- Tailor made flexible solutions in all important aspects

Zero Emission Hydrogen Turbine Center


The zero emission demonstrator plant at the gas turbine test facility in Finspång, Sweden

- Use of **excess power** from turbine test runs to produce hydrogen in an **electrolyzer**
- **Solar panels** for continuous green hydrogen production
- A **micro grid** together with **batteries for backup**
- Utilization of the produced hydrogen as a turbine fuel for upcoming turbine tests to **reduce our own LNG consumption and provide inhouse testing of 3D-printed hydrogen burners**

Three-year project with funding from EU

- **Start of operation in 2021**
- Supports Siemens Energy's efforts in achieving
 - **100% hydrogen ready gas turbines by 2030**
 - **climate neutral own operations by 2030**
 - **green electricity 100% of own power consumption by 2023**
- Funded by the six partners and EU project **ERA-Net Smart Energy Systems** program through the **Swedish Energy Agency**

The future energy system on display



SIEMENS
energy

CHALMERS
UNIVERSITY OF TECHNOLOGY



ALMA MATER STUDIORUM
UNIVERSITÀ DI BOLOGNA



LÄNSSTYRELSEN
ÖSTERGÖTLAND



FINSPÅNG

THE LINDE GROUP


EU-funded HYFLEXPOWER Project

100% H₂ gas turbine in DLE mode demonstrated in Sept. 2023



World-first demonstration of a **power-to-H₂-to-power** path for **CO₂-free** power generation pilot including an advanced DLE H₂ gas turbine

- Decarbonizing papermill by modernizing combined heat and power plant in Saillat-sur-Vienne, France.
- Siemens Energy led consortium of EU funded 4-year project until 2024



Source: <http://www.hyflexpower.eu/>

Milestones

2021

- Installation of the H₂ production, storage & supply facility at site

2022

- Initial demonstration of advanced plant concept with NG/H₂ mixtures up to 30%

2023

- Demonstration of up to **100% H₂ for carbon-free energy production** from stored excess renewable energy successfully demonstrated in Sept. 2023


HYFLEXPOWER 100% Hydrogen Gas Turbine DLE Combustion System Development

SIEMENS
ENERGY

High Fidelity Simulations

Full system assessment

Massively parallel computations
with >1,000 CPUs for ~2 weeks



Automated design optimization

Enabling > 1,000 design iterations

Rapid Prototyping using AM

Additive manufacturing enables

- Monolithic prints
- Complex internal purging features for extended flashback margin
- Internal cooling features
- Advanced mixing concepts for low emissions
- Fast design iterations due to rapid prototyping

26 Hardware variants have been tested

Iteration Loop

Design Validation

High-pressure combustion tests at Clean Energy Center (CEC) in Berlin



48 Test Days In 5 campaigns


2 x SGT-400 engine tests at customer site



2 Test Campaigns with Natural Gas in Lincoln

Developed and Demonstrated DLE combustion system with 100% H2 at SGT-400 engine conditions

EU Clean Hydrogen Partnership: HyCoFlex Project Executive Summary and Consortium Partners



Demonstration of the power-to-H₂-to-power **cogeneration plant** with an **H₂ gas turbine** for flexible operation with **NG/H₂ fuels up to 100% H₂**

- HyCoFlex project will utilize and advance the infrastructure of the HYFLEXPOWER advanced plant concept

• Key Targets

- 100% H₂ capability without derate
- Operate on blends of H₂ and NG from 0-100% H₂
- <25 ppm NO_x (without SCR).
- Efficiency to be within 0.5%-2.0% at 100% load.
- Achieve minimum load ramp-rate of 10% @100% H₂
- Accommodate H₂ fluctuations ±30% vol./min.
- At least 60 cumulative fired hours of H₂ operation.

- Overall budget: ~ 10.2 M€
- EU contribution: ~ 4.44 M€
- UK contribution: ~ 1.56 M€
- Project Start: February 1, 2024 | End Date: October 31, 2026

This project is supported by the Clean Hydrogen Partnership and its members Hydrogen Europe and Hydrogen Europe Research (GA 101138002).

This project is co-funded by UK Research and Innovation.



Siemens Energy is the right partner for hydrogen-fueled gas turbines in a sustainable, hydrogen-based energy world

Hydrogen capabilities in Siemens Gas Turbines

- All newly built Siemens Energy gas turbine types capable to burn different levels of hydrogen in the fuel mix
- Smaller hydrogen contents not requiring any modification compared with standard natural gas turbines (new unit applications)
- Operating gas turbines¹ (field installations) able to be upgraded to burn hydrogen
- Siemens Energy with a roadmap in implementation to burn 100% hydrogen fuel in gas turbines



¹ Limits to be evaluated

May 2024

Conclusions



Existing assets and future **investments** in gas turbines are **protected** also in a fully decarbonized world



Carbon-free power generation in gas turbines with green hydrogen



Hydrogen-capable gas turbines with **increased fuel flexibility** to burn both hydrogen and natural gas



Siemens Energy gas turbines **fully compliant** with **emission limits** when burning hydrogen

Contact page

Dr. Adnan Eroglu

Senior Principal Key Expert R&D
SE GS C LGT EN MOD EE

Mobile: +41 79 770 54 58

adnan.eroglu@siemens-energy.com

[Siemens Energy H₂ web page](#)



Disclaimer



This document may contain statements relating to the future business and financial performance and future events or developments involving Siemens Energy (together with its subsidiaries, "Siemens Energy") that may constitute forward-looking statements. These statements may be identified by words such as "expect," "look forward to," "anticipate," "intend," "plan," "believe," "seek," "estimate," "will," "project" or words of similar meaning. Such statements are based on the current expectations and certain assumptions, of which many are beyond Siemens Energy's control. These are subject to a number of risks and uncertainties. Should one or more of these risks or uncertainties materialize, should decisions, assessments or requirements of regulatory authorities deviate from our expectations, or should underlying expectations not occur or assumptions prove incorrect, actual results, performance or achievements of Siemens Energy may (negatively or positively) vary materially from those described explicitly or implicitly in the relevant forward-looking statement. Siemens Energy does not intend, nor assume any obligation, to update or revise these forward-looking statements in light of developments which differ from those anticipated.

The information and opinions contained in this document are provided as at the date of this presentation and are subject to change without notice. They do not purport to contain all information that may be required to evaluate Siemens Energy and have not been verified independently. The information in this document is of a preliminary and abbreviated nature and may be subject to updating, revision and amendment, and such information may change materially.

This document contains forecasts, statistics, data and other information relating to markets, market sizes, market shares, market positions and other industry data on Siemens Energy's business and markets (together the "market data") provided by third party sources as interpreted by us. This market data is, in part, derived from published research and additional market studies prepared primarily as a research tool and reflects estimates of market conditions based on research methodologies including primary research, secondary sources and econometric modelling, which may not be representative.

Nothing contained in this document (and the appertaining verbal presentation, if any) is a warranty, guarantee or representation. All statements, data and information contained herein (and the appertaining verbal presentation, if any) are non-binding and shall not create on Siemens any commitment, obligation or liability whatsoever. Furthermore, they shall not be ground for any claim or argument, regardless whether based on this document (and the appertaining verbal presentation, if any) alone or in connection with a separate agreement or contract.

Subject to changes and errors. The information given in this document only contains general descriptions and/or performance features which may not always specifically reflect those described, or which may undergo modification in the course of further development of the products. The requested performance features are binding only when they are expressly agreed upon in the concluded contract.

All performance at ISO conditions is estimated and not guaranteed.

Trademarks mentioned in this document are the property of Siemens Energy AG, its affiliates or their respective owners.